

t4000

Through The Wall Solution



HANTLE

The **Hantle t4000** ATM provides an economical, high performance through-the-wall solution. Designed and built with compact **modular** components and engineered for **easy installation**.

The t4000 offers a host of high-end features including a **10.4" Sun-Viewable Color LCD** supporting custom screen advertisements and communication via **56K Modem** or integrated **Ethernet (SSL)**.

The t4000 is **TDES** and **ADA** compliant out of the box, including a **PCI/VISA/Interac certified encrypting PIN pad (EPP)**, a voice guidance system, and lighted action indicators.

HANTLE

"Tomorrow's Technology for Today's Market"

ATM H
ATMHELPERS
You're... At The Money!
1-888-895-8239

t4000

HANTLE
www.hantle.com

INTEGRATED ILLUMINATED TOPPER

Integrated illuminated topper
for creating high visibility
and attracting customers

HIGH-BRIGHT MONITOR

10.4 inch diagonal 32-bit color, backlit
Sun-viewable TFT LCD panel
800 x 600 SVGA resolution

ADA

Accessible keypad layout
Voice guidance
Lighted action indicators



PRINTER

3 1/8" Thermal receipt printer.
Can print custom graphic

CARD READER

Manual insert (dip) magnetic card reader
EMV (optional)

KEYPAD

16-key alphanumeric keypad
VISA/Interac PCI certified
Triple DES (TDES) compliant
Encrypting PIN pad (EPP)

CPU

Intel XScale® 32-bit CPU
Windows® CE operating system

REAR SERVICE PANEL

Perform Operator Tasks and Diagnostics

CASH DISPENSER

Sliding cash dispensing unit for easy service
1,700 note removable cassette



COMMUNICATION

56K dial-up modem or Ethernet (TCP/IP)
On-board SSL Encryption

SECURITY

UL 291 Business Hour listed
Electronic lock
Cencon Lock (optional)

ADVANCED SERVICES

The Hantle t4000 comes with a steel pedestal which can be adjusted from 25" to 35". The pedestal carries the entire weight of the machine so you can install the t4000 in thin walls or facades.

SPECIFICATIONS

Dimensions

33" H 24" W 28" D

Weight: 400 lbs*

*includes pedestal

Operating Environment:

Temperature range: 40°F-95°F

Relative humidity: Non-condensing - 15%-85%

Options and Upgrades:

Cencon Electronic Lock

EMV Card Reader

